



Phones: +381 63 658 074 / +381 64 27 54 268

Email: [info@decachem.com](mailto:info@decachem.com)

## Technical Data Sheet Eastman™ Ethylene Glycol, Polyester Grade

### Applications

- Chemicals & petrochemicals

### Key Attributes

- Good Solvent Characteristics
- High boiling point
- Hygroscopic
- Moderate Viscosity
- Noncorrosive

### Product Description

Eastman™ Ethylene Glycol, Polyester Grade is a high purity grade of ethylene glycol with excellent appearance and clarity. Eastman™ Ethylene Glycol, Polyester Grade is used for manufacturing polyester fibers, polyethylene terephthalate (PET) resins, and other materials. End products include water and drink bottles, textiles, and carpet fiber. Eastman™ Ethylene Glycol is a clear, odorless, moderately viscous, hygroscopic, and high boiling liquid. Its properties make it useful for various applications including heat transfer fluid, antifreeze, and conditioning agent.

### Typical Properties

Property	Typical Value, Units
<b>General</b>	
Acidity as Acetic Acid	0.002 wt % max.
Assay	99.9 wt % min.
Autoignition Temperature	410 °C (770 °F)
Boiling Point @ 760 mm Hg	197 °C (387 °F)
Color Pt-Co	5 max.
Critical Pressure	8200 kPa
Critical Temperature	446 °C
Critical Volume	0.187 L/gmol
Empirical Formula	C <sub>2</sub> H <sub>6</sub> O <sub>2</sub>
Evaporation Rate (n-butyl acetate = 1)	< 0.01
Expansion Coefficient, per °C @ 10-40°C	0.00070
Explosive Limits in Air Lower	3.10 Vol %
Upper	42.0 Vol %
Flash Point Closed Cup	111 °C (232 °F)
Freezing Point	-13 °C (9 °F)
Hansen Solubility Parameters	
Hydrogen Bonding	26.0 MPa <sup>1/2</sup>
Nonpolar	17.0 MPa <sup>1/2</sup>
Polar	11.0 MPa <sup>1/2</sup>
Total	33 MPa <sup>1/2</sup>

# DECACHEM DOO, Novi Sad, Serbia

Address: Lozionicka 14/9, 21000 Novi Sad, Serbia ;  
PIB: 113353206    Matični broj: 21851396

[Http://www.decachem.com](http://www.decachem.com)



Phones: +381 63 658 074 / +381 64 27 54 268

Email: [info@decachem.com](mailto:info@decachem.com)

Heat of Combustion	-1053 kJ/g-mol
Heat of Vaporization at Boiling Point	53.1 kJ/g-mol
Liquid Heat Capacity @ 25°C	150 J/(mol K)
Liquid Viscosity @ 25°C	17 cP (mPa·s)
Molecular Weight	62.07
Refractive Index @ 25°C	1.4307
Specific Gravity @ 20°C/20°C	1.1157
Solubility in Water, @ 20°C	Complete
Water in, @ 20°C	Complete
Surface Tension @ 20°C	48 dynes/cm
Vapor Density (air = 1)	2.1
Vapor Pressure @ 20°C	0.06 mm Hg
@ 55°C	1 mm Hg
Wt/Vol @ 25°C	1.11 kg/L (9.26 lb/gal)

## Compatibility and Solubility

Miscible with water, alcohols, aldehydes.

## Handling Precautions

Slight irritant to skin and eyes. Irritating in case of inhalation. Hazardous in case of ingestion. Ethylene Glycol is not compatible with oxidizing agents, strong acids, strong bases, aliphatic amines, isocyanates, chlorosulfonic acid, and oleum. Ethylene Glycol should be kept away from sources of ignition, smoking, and open flames.

## Packaging

Bulk

## Storage

If trace iron or color contamination is of concern, a stainless steel, aluminum, or epoxy liner storage vessel is recommended. A nitrogen blanket with slight positive pressure is recommended to prevent trace water or the accumulation of trace impurities through oxidation. The freezing point of ethylene glycol is -13°C, and heating or insulation is recommended at cold temperatures. Contact with rubber, zinc, copper, and tin are not recommended.